

PF-e™

Self-Cleaning Filter Enhancement System

PRODUCT DESCRIPTION

The PF-e from GPS Air is an indoor duct mounting filter enhancement system. The Opti-Lok™ technology improves an air filters ability to capture sub-micron particles, making it more efficient. It's low profile design allows for mounting on typical outdoor air and return ducts.

STANDARD FEATURES

- Opti-Lok™ technology
- Multi-voltage input
- Self-cleaning cycle
- Operation status LED
- Surface sealing face gasket
- 7/8" hole for sized for 1/2" trade size conduit fitting
- Integral Building Automation System (BAS) alarm contacts



SPECIFICATIONS

Input Voltage	24-240 VAC	Unit Dimensions	5.4" L x 5.4" W x 3.8" H (overall), 2.0" H (in-duct)
Frequency	50/60 Hz	Weight	1.1 lb
Power Consumption	11W (operating), 14W (cleaning cycle)	Alarm Contact Rating	250 VAC / 1A, N.O. "dry" contact
Airflow Capacity	0 - 3,800 CFM	Electrical Listings	UL, cUL
Temperature / Humidity Range	-20°F to 140°F / 0 - 100% RH	Compliance & Certifications	UL 867, UL 2998, CARB, FCC part 18
Compatible Filter Types	Electrostatic Filters using Synthetic Media		