

## Self-Cleaning Filter Enhancement System

### PRODUCT DESCRIPTION

The PF-i from GPS Air is a self-cleaning filter enhancement system. The Opti-Lok™ technology improves an air filter's ability to capture sub-micron particles, making it more efficient. The unit is designed for mounting inside ducts and air handling units upstream of system filtration.

### STANDARD FEATURES

- Opti-Lok™ technology
- Multi-voltage input
- Self-cleaning cycle
- Magnets for ease of installation
- Integral Building Automation System (BAS) alarm contacts



### SPECIFICATIONS

<b>Input Voltage</b>	24-240 VAC	<b>Unit Dimensions</b>	7.3" L x 2.0" W x 4.3" H
<b>Frequency</b>	50/60Hz	<b>Weight</b>	1.42 lb
<b>Power Consumption</b>	11W (operating), 14W (cleaning cycle)	<b>Alarm Contact Ratings</b>	250 VAC / 1A, N.O. "dry" contact
<b>Airflow Range</b>	0 - 3,800 CFM	<b>Electrical Listings</b>	ETL (us, c)
<b>Temperature / Humidity Range</b>	-20°F to 140°F / 0 - 100% RH	<b>Compliance &amp; Certifications</b>	UL 867, UL 2998, CARB, FCC part 18
<b>Compatible Filter Types</b>	Electrostatic Filters using Synthetic Media		